

# Transit Packaging Monitor Labels

## Drop'n Tel

The Drop'n Tel System includes two warning labels and is manufactured in six different G-ranges (5G, 10G, 15G, 50G and 100G). The device monitoring five times the force of gravity is very sensitive.



The device monitoring 100 times the force of gravity requires a greater impact to activate. Attach the Drop'n Tel to your product by removing the liner on the back to expose the adhesive or screw/nail it using the holes on each end.

Weight in Pounds	Container Area in Cubic Feet				
	0-1	1-5	6-15	16-50	50+
0-10	100G	100G	50G	50G	25G
11-25	100G	50G	50G	25G	25G
26-50	50G	25G	25G	25G	25G
51-100	50G	25G	25G	15G	15G
101-250	25G	25G	15G	15G	15G
250-1000	15G	10G	10G	10G	10G
1000+	5G	5G	10G	10G	10G

The chart should only be used as a guide. Drop'n Tel activation depends upon the type and amount of cushioning used to protect a product in transit. Drop height will also affect activation.

## Tip'n Tel

Tip'n Tel is a brightly coloured device that product handlers quickly recognise. It includes a system of labels that warns all handlers of a monitoring device. The Tip'n Tel can be mounted on the inside or outside of your shipment. The Tip'n Tel is activated by pulling the bar in the centre of the device.



Attach it to either your product or shipping container by removing the liner on the back to expose the adhesive. You may also attach the Tip'n Tel by nailing or stapling it to the container. If your product is tipped slightly less than 90 degrees or beyond, the clear arrow becomes permanently blue. Your customer can then immediately check for damage.

## Tilt Watch

Tilt Watch is a state-of-the-art monitor that will indicate red if your container has been tilted on its side or completely opened. Normal movement or road shock will have no effect. Tilt Watch will not activate due to acute take off angles in aircraft. It's fair to you and your carriers. The Tilt Watch incorporates a vacuum seal that eliminates any effects of humidity or temperature changes. The self-stick backing utilises the most aggressive 5mm acrylic adhesive available assuring a permanent bond on all but the roughest containers. When used with its 5" x 8" companion label, the contact area is increased (along with its visibility), which forms a more permanent bond to the host of the container.



Tilt Watch is the best choice for goods that must remain upright to ensure intact delivery. Tilt Watch is "carrier-friendly" and guarantees 100% accuracy. It is an affordable and reliable solution to monitoring and controlling the shipping attitude of heavy machinery, large computers, electronic panels, cut flowers, batteries, liquids and a host of other products.

## Shock Watch

A self adhesive label measuring 100mm incorporating a glass tube which activates by turning red when the article to which it has been attached is dropped from above to a pre-determined height.



There are five colour coded sensitivities designed to activate at certain drop heights. The Shock Watch sensitivity should be based on product fragility, container cushioning type and design. Field trials are recommended to determine the correct sensitivity relative to product damage.

Code	Colour	Average cm	Activation height (inches)	g Rating (approx)
L-30	Green	120	47	100
L-35	Orange	90	35	75
L-47	Red	47	18	50
L-55	Purple	33	13	38
L-65	Yellow	30	11	20