

# Strapping

## Machine Strapping

- To be used on semi and fully automatic Strapping Machines
- Available in a range of colours on request
- Printed Strapping also available on request (subject to minimum quantity)

| Product code | Size         | Core size | Packed | Thickness (mm) | B/S (kg) | Colour     |
|--------------|--------------|-----------|--------|----------------|----------|------------|
| MS5          | 5mm x 6300m  | 200/190mm | 2      | 0.50           | 50       | White      |
| MS6          | 6mm x 5000m  | 200/190mm | 2      | 0.63           | 70       | White/Blue |
| MS8          | 8mm x 4000m  | 200/190mm | 2      | 0.63           | 80       | White/Blue |
| SMC0940S     | 9mm x 4000m  | 200/190mm | 2      | 0.55           | 85       | White/Blue |
| MS9H         | 9mm x 4000m  | 200/190mm | 2      | 0.63           | 100      | White/Blue |
| SMC1230S     | 12mm x 3000m | 200/190mm | 2      | 0.55           | 130      | White/Blue |
| MS12H        | 12mm x 2500m | 200/190mm | 2      | 0.63           | 150      | White/Blue |
| SMC1225S     | 12mm x 2500m | 200/190mm | 2      | 0.55           | 130      | White/Blue |

- Other sizes/thickness available on request

## Automatic & Semi Automatic Strapping Machines



### TMS 300

- Standard Semi Automatic Strapping Machine
- Enclosed Frame
- For strap widths 6mm-15.5mm



### XCS 550

- Semi Automatic Strapping Machine
- Unique Frame Design
- Height adjustable
- For strap widths 5mm-13mm



### TRS 600

- Automatic Strapping Machine
- Strapping speed: 27 straps/minute (60Hz)
- Outside tension control
- Short feed sensor for strap widths 9-12mm

### AFS 900

Same features as TRS 600 plus:

- Auto strap feeding
- Auto strap re-feed