

Electric and Battery Powered Sealless Strapping Tools



P320

P320 Battery powered friction weld strapping tool is simple to operate, both straps are inserted into the tool together making strap threading easy. Thanks to the battery operation, the working range is extended independent of any power supply. The sealing time is adjustable to give optimum seal efficiency. The P320 can be set to the specific strap specification to improve the tool performance and increase the number of strap cycles per battery charge. The individual tension adjustment enables you to achieve the correct strap tension to reduce load movement.

Strap Specification

- For polypropylene and polyester. Widths 10mm-16mm. Thicknesses 0.40mm-1.05mm (Please specify when ordering).
- Strap tension. Fully adjustable from 400n-2000n (max tension depends on strap spec.)
- Tension speed. 270mm/second
- Tool weight. 4.2kgs (9.25lb) including battery without suspension bracket

Accessories

- P32.0111 Bottom base wearing protection plate
- P32.0112 Suspension bracket for standard working position
- TB46 Tool balance with safety device 4-6Kgs 2mtr stroke
- N5.4410 P320 Battery Charger - Recharging time 25 minutes
- N5.4307 P320 Battery 12v 2.4Ah - Battery life approx 3000 charges
- 110 volt available on request

P321

P321 Battery powered high tension weld strapping tool is simple to operate, both straps are inserted into the tool together making strap threading easy. The P321 applies exceptional tension up to 3000n with ease. Thanks to the battery operation, the working range is extended independent of any power supply. The sealing time is adjustable to give optimum seal efficiency. The P321 can be set to the specific strap specification to improve the tool performance and increase the number of strap cycles per battery charge. The individual tension adjustment enables you to achieve the correct strap tension to reduce load movement.

Strap Specification

- For polypropylene and polyester. Widths 16mm-19mm. Thicknesses 0.40mm-1.05mm (Please specify when ordering).
- Strap tension. Full adjustable from 600n-3000n (max tension depends on strap spec.)
- Tension speed. 280mm/second
- Tool weight. 4.3kgs (9.5lb) including battery without suspension bracket

Accessories

- P32.0127 Bottom base wearing protection plate
- P32.0112 Suspension bracket for standard working position
- P32.0137 Combination suspension bracket for standard vertical & horizontal working positions
- P32.1129 Control knob kit for the permanent setting of strap tensioning & sealing time
- TB46 Tool balance with safety device 4-6Kgs 2mtr stroke
- N5.4410 P321 Battery Charger - Recharging time 40 minutes
- N5.4309 P321 Battery 14.4v 2.4Ah - Battery life approx 3000 charges
- 110 volt available on request